**Specification Sheet** 



## DESCRIPTION

Model: \_

Professional-grade low voltage in-ground fixture. Installs in-ground at grade level for concealed appearance. Model grate-protected lens for use in areas where lens could be scratched or impacted by aggregate, mulch, etc. Combines rugged brass lens with non-corrosive polymer body. Suitable for installation in landscape or hardscape areas. Avoid placing directly in areas where pedestrian or vehicular equipment can directly contact fixture. Lamp sold separately.

MODEL: LW-GL260K | MR16 WELL LIGHT

## PRODUCT FEATURES


Material	Solid Cast Brass Lid
Lamp Type	Low Voltage MR16
Finish	Aged Brass Finish

## SPECIFICATIONS

- Lid: Grated cast brass, attached with 4 color matched stainless steel screws
- Lens: Clear glass lens
- Base: Non-corrosive poly housing
- **Connectors:** (2) A-LOC waterproof wire connectors, (2) copper crimps included
- Wire Lead: 36" wire lead pre-connected to the fixture, 16 awg (UL listed), black
- Socket: Spring-loaded ceramic bi-pin MR16, with dual contacts and lamp clips
- · Warranty: Lifetime warranty on fixture housing
- Certifications: Complies with the requirements of UL-1838 and CAN/CSA-C22.2 No. 250.7 Identified with the ETL and cETL listed mark

## DIMENSIONS

Lid Diameter	4.87 in (12 cm)
Lid Height	1 in (2 cm)
Fixture Height	5.75 in (15 cm)
Base Diameter	3.5 in (9 cm)
Ship Weight	2.13 lbs (34 oz)





Type: